
















分频器 Crossover List



NO.	Model	Image	Specifications	Price
01	F-2A		Maximum power:500W Impedance:4-8Ω Characteristics:2 way(TW) Size:155mm X 100mm	
02	PA-2		Maximum power:400W Impedance:4-8Ω Characteristics:2 way(TW) Size:145mm X 90mm	
03	AP-5		Maximum power:400W Impedance:4-8Ω Characteristics:2 way(TW) Size:145mm X 90mm	
04	PA-3		Maximum power:400W Impedance:4-8Ω Characteristics:3 way(TMW) Size:145mm X 90mm	
05	AP-2B		Maximum power:500W Impedance:4-8Ω Characteristics:2 way(TW) Size:170mm X 120mm	
06	PA-280JBL		Maximum power:800W Impedance:4-8Ω Characteristics:2 way(TW) Size:170mm X 120mm	
07	PA-280JBL+		Maximum power:800W Impedance:4-8Ω Characteristics:2 way(TW) Size:170mm X 120mm	

08	PA-290		Maximum power:800W Impedance:4-8Ω Characteristics:2 way(TW) Size:170mm X 120mm	
09	PA-2T		Maximum power:1000W Impedance:4-8Ω Characteristics:2 way(TW) Size:175mm X 125mm	
10	PA-25T		Maximum power:1000W Impedance:4-8Ω Characteristics:3 way(TWW) Size:175mm X 125mm	
11	PA-3T		Maximum power:1000W Impedance:4-8Ω Characteristics:3 way(TMW) Size:175mm X 125mm	
12	PA-28T		Maximum power:800W Impedance:4-8Ω Characteristics:3 way(TWW) Size:200mm X 135mm	
13	PA-2215		Maximum power:400W Impedance:4-8Ω Characteristics:3 way(TWW) Size:150mm X 120mm	
14	3388		Maximum power:800W Impedance:4-8Ω Characteristics:3 way(TMW) Size:160mm X 110mm	
15	2A80		Maximum power:800W Impedance:4-8Ω Characteristics:3 way(TW) Size:160mm X 110mm	

16	6A80		Maximum power:600W Impedance:4-8Ω Characteristics:3 way(TWW) Size:170mm X 120mm	
17	PA-2528		Maximum power:1000W Impedance:4-8Ω Characteristics:3 way(TWW) Size:186mm X 160mm	
18	PA-2218D		Maximum power:1000W Impedance:4-8Ω Characteristics:3 way(TWW) Size:175mm X 120mm	
19	K-2218N		Maximum power:500W Impedance:4-8Ω Characteristics:3 way(TWW) Size:145mm X 95mm	
20	SRX-725		Maximum power:500W Impedance:4-8Ω Characteristics:3 way(TWW) Size:210mm X 120mm	
21	SRX-715		Maximum power:500W Impedance:4-8Ω Characteristics:2 way(TW) Size:170mm X 114mm	
22	F-125		Maximum power:500W Impedance:4-8Ω Characteristics:2 way(TW) Size:170mm X 160mm	

23	F-225		Maximum power:1000W Impedance:4-8Ω Characteristics:3 way(TWW) Size:200mm X 135mm	
24	XR-9025		Maximum power:1200W Impedance:4-8Ω Characteristics:3 way(TWW) Size:220mm X 135mm	
25	XR-9015		Maximum power:500W Impedance:4-8Ω Characteristics:2 way(TW) Size:180mm X 120mm	
26	OL-200		Maximum power:200W Impedance:4-8Ω Characteristics:2 way(TW) Size:113mm X 85mm	
27	3B		Maximum power:350W Impedance:4-8Ω Characteristics:3 way(TMW) Size:120mm X 90mm	
28	T-2505		Maximum power:200W Impedance:4-8Ω Characteristics:2 way(TW) Size:137mm X 90mm	
29	WV-150		Maximum power:800W Impedance:4-8Ω Characteristics:1 way(W) Size:125mm X 120mm	
30	S-200		Maximum power:1200W Impedance:4-8Ω Characteristics:1 way(W) Size:125mm X 123mm	

31	T-250		Maximum power:1200W Impedance:4-8Ω Characteristics:2 way(WW) Size:200mm X 120mm	
32	T-9988		Maximum power:350W Impedance:4-8Ω Characteristics:3 way Size:88mm X 70mm	
33	T-100		Maximum power:350W Impedance:4-8Ω Characteristics:1 way(W) Size:88mm X 70mm	
34	F-500		Maximum power:200W Impedance:4-8Ω Characteristics:2 way(TW) Size:90mm X 65mm	
35	JDD-600		Maximum power:200W Impedance:4-8Ω Characteristics:2 way(TW) Size:90mm X 65mm	
36	M-450		Maximum power:250W Impedance:4-8Ω Characteristics:1 way(T) Size:120mm X 90mm	
37	140-796		Maximum power:300W Impedance:4-8Ω Characteristics:1 way(T) Size:150mm X 100mm	
38	T-3		Maximum power:150W Impedance:4-8Ω Characteristics:1 way(T) Size:72mm X 65mm	

39	WA-450		Maximum power:120W Impedance:4-8Ω Characteristics:way(T) Size:155mm X 100mm	
40	WA750		Maximum power:120W Impedance:4-8Ω Characteristics:way(T) Size:155mm X 100mm	
41	T-101		Maximum power:150W Impedance:4-8Ω Characteristics:1 way(T) Size:85mm X 80mm	
42	T-102		Maximum power:250W Impedance:4-8Ω Characteristics:1 way(T) Size:90mm X 90mm	
43	BD2		Maximum power:800W Impedance:4-8Ω Characteristics:1 way(W) Size:180mm X 140mm	
44	BD2A			
45	T-2088		Maximum power:200W Impedance:4-8Ω Characteristics:2 way(TW) Size:70mm X 50mm	
46	JD-3C15M		Maximum power:500W Impedance:4-8Ω Characteristics:3 way(TMW) Size:140mm X 108mm	
47	JD-3325		Maximum power:1000W Impedance:4-8Ω Characteristics:3 way(TWW) Size:200mm X 120mm	

48	KP-6012		Maximum power:500W Impedance:4-8Ω Characteristics:2 way(TW)	
49	K-2000		Maximum power:450W Impedance:4-8Ω Characteristics:2 way(TW)	
50	EVP-15		Maximum power:600-1000W Impedance:4-8Ω Characteristics:2 way(TW) Size:180mm X 130mm	
51	JBL-715		Maximum power:600-1000W Impedance:4-8Ω Characteristics:2 way(TW) Size:200mm X 123mm	
52	JBL-725		Maximum power:600-1000W Impedance:4-8Ω Characteristics:3 way(TWW) Size:200mm X 123mm	